

KERSHAW 44-2 ROTARY SCARIFIER

OVERVIEW

The Kershaw® 44-2 Rotary Scarifier is a self propelled machine designed to remove ballast, wood chips, and other debris from the cribs where old ties have been removed.

DIMENSIONS

| | |
|--------|------------|
| Weight | 18,000 lbs |
| Length | 24' 2" |
| Width | 11' 6" |
| Height | 8' 9" |

PERFORMANCE

Frame: The frame is off all welded construction using structural channel and formed plate.

Engine: Caterpillar C4.4, 131hp @ 2200 rpm Tier IV Final Propel System: 3" (76 mm) diameter solid axles with chain drive from separate hydraulic motors driving both axles.

Travel Speed: 20 mph (32 km/hr). Two (2) propel drive motors for quicker response in work mode. #100 drive chain with hardened tooth sprockets. Heavy duty axle bearings.

Wheels and Brakes: 16" (406 mm) cast steel wheels. External, individual composite brake shoes applied directly on centerline of wheel tread. Service brakes are air applied, spring released. Emergency/parking brakes are spring applied, air released.

SYSTEMS

Electrical System: 24VDC negative ground. System maintained by engine driven alternator. Color coded and numbered wiring.

Hydraulic System: Pressure compensated piston type pump direct coupled to engine. Hydraulic oil is filtered through a 100 mesh (145 micron) suction screen and 10 micron return line filter. Manifold- type stack valves for improved serviceability. Electric emergency pump.

Air System: A 12 cfm (.34 m³/min) @1,250 rpm air compressor, engine oil lubricated, air-cooled; pressure - 100 - 120 psi (609 - 927 kPa), 15 gallon air tank.

OTHER FEATURES

Options: Large enclosed cab with 99.5 cubic foot capacity. Ergonomically designed seat. Large front windshield with unobstructed view of operation. Hydraulic pilot-pressure bottom-ported joystick controls on operator seat with heat shields. Self-contained hydraulically driven air conditioner/heater/ pressurizer unit mounted on rear wall of cab (roof mount optional)

Options: Non-insulated wheels, Rotary head extension, yard work head extension, tie inserter winch with sweeper/ kicker, rock axle kit, rear rubber padded bumpers.

