

# **Tiger**™ ROTARY AND FLAIL **RailKut**



## **Productivity. Performance. Power.**

With the power and versatility of this innovative machine you can mow along rail, trim low branches or clear a highway intersection. Once job is done, you can drive the RailKut at highway speeds, improving overall productivity. Available in 22' and 24' boom lengths.



**DURABILITY INNOVATION**  
**COMMITMENT**





Features include right side viewing camera. Standard equipment on the RailKut. Allows operator clear view of cutter head in operation while facing forward and steering vehicle.



Viewing Monitor located in cab of truck.

# Tiger Specifications

## Truck

### F550 TRUCK SAFETY FEATURES

#### Four Wheel Drive Truck

Engine Turbo 8 cyl. Diesel  
 Horsepower 325 HP @ 3,300 RPM  
 Fuel Tank 40 gallon, Supplies Both Engines  
 Steering Dual Station, Power  
 Hyrail System Bolt On Rated to 28,000 lbs.  
 Manual Locking, Up and Down  
 Brakes Hydraulic Front

Master ON/OFF Switch  
 Operator Presence Switches on Right Side Door  
 Mower Safety Start Switch  
 Brush Guard Extending Over Cab  
 Operator Protective Screen Covers Right Hand Door  
 Manual Emergency Over-ride

**Accessories**  
 Snowblower  
 Saw Blade  
 Tree Shear and Auger  
 Fire Suppression  
 Turbine Blower  
 Boom Sweeper

#### RailKut

Engine Type Tier 4 Final 4 Cyl., Turbo Diesel  
 Horsepower 74 HP @ 1,800 RPM  
 Throttle Control Electronic Adjustable  
 Hydraulic System 45 GPM @ 3,250 PSI  
 Safety Stop 7 Second Shut Down  
 Truck Bed Quick Removable



SNOW BLOWER



SAW BLADE



TIGER AUGER



TREE SHEAR

#### Standard Equipment

Spare Tire and Rim  
 Torque Wrench with Rotary head  
 Directional Light Bar  
 Emergency Hyrail Retract



OPTIONAL TRAILER HITCH



FIRE SUPPRESSION



TURBINE BLOWER



BOOM SWEEPER



DITCHER

## Boom Mower

### RK-22 RK-24 ROTARY FLAIL

	RK-22	RK-24		ROTARY	FLAIL
Cutter Reach Up	19' 10"	21' 2"	Cutting Width	50"/ 60"	50"/ 63"
Cutter Reach Out	21' 6"	23' 2"	Cutting Head Weight	785 lbs. (Minimum)	835 lbs. (Minimum)
Cutter Reach Down	12' 5"	13' 5"	Cutting Assembly	One-piece forged alloy spindle with stationary wire guards and a one-piece formed dishpan.	61" knife swing circumference 2,200 RPM cutter shaft
Controls	Electronic Joystick	Electronic Joystick	Blade Options Full Swing	Two, Three, Four or Six	24 cast, 33 oz. knives 48 all-purpose knives
Transport Width	8' 6"	8' 6"	Brush	5/8" x 5" x 17.125"	
Transport Stow Height	11' 8"	13' 5"	Grass (High Suction)	5/8" x 5" x 17.125"	



RELAMINC.COM

RELAM, Inc.  
 7695 Bond Street  
 Glenwillow, Ohio 44139  
 800.962.2902  
 quotes@relaminc.com



WISKTRUCKS.COM

Wiskerchen Truck & Equipment  
 205331 Co Rd F  
 Spencer, WI 54479  
 888.405.0110  
 info@wisktrucks.com

Rev 07-24